

Request for operation completion with the full pre-authorization amount, monetary funds and points (autoCompletion.do)

The request used for completion is `autoCompletion.do`.

Request parameters

Name	Type	Mandatory	Description
userName	AN..30	Yes	Login of the service account of the merchant. If login and password are used for authentication during token registration, then the token parameter does not need to be passed.
password	AN..30	Yes	Merchant's service account password. If login and password are used for authentication during token registration, then the token parameter does not need to be passed.
orderId	ANS36	Yes	Identifier of the order in the payment system. It is unique within the system. Missing if order registration failed due to an error detailed in <code>ErrorCode</code> .
compositeCompletionAmount	N..20	Yes	The amount to be debited, consisting of the amount in money and the amount of points. The amount can be equal to or less than the order remaining amount. If zero is passed in this parameter, completion will occur for the entire pre-authorized amount.

Response parameters

Name	Type	Mandatory	Description
errorCode	ANS..3	Yes	Error code. Can be missing if the result has not caused an error.
errorMessage	AN..512	Yes	Error description in the language passed in the <code>language</code> parameter in the request.
pcId	AN..512	No	Loyalty processing transaction identifier.

Name	Type	Mandatory	Description
operation	AN..512	No	Operation type, the following values are possible: <ul style="list-style-type: none"> • PAYMENT; • AWARD; • REVERSE; • REFUND_PAYMENT; • REFUND_AWARD.
transactionId	AN..512	No	The identifier of the transaction in the payment gateway.
amount	String	No	Amount in points.
successful	AN..512	No	A feature of the success of the operation, the following values are possible: <ul style="list-style-type: none"> • true (successful); • false (unsuccessful).

Request example

```
userName=login&password=password&orderId=94e86702-d37a-44dc-b953-36f75f80507b&compositeCompletionAmount=90000
```

Response example

```
{"operations":[{"pcId":2699110,"operation":"REFUND_PAYMENT","amount":20,"successful":true,"transactionId":"1642"},{"pcId":2699111,"operation":"REFUND_AWARD","amount":10180,"successful":true,"transactionId":"1643"}],"errorCode":0"}
```