

Request for recurrent payments (recurrentPayment)

The request used for registering an order is `recurrentPayment.do`

In this document, the following data type conventions are used when describing request and response parameters:

- A<n> - a sequence of Latin letters of length <n>;
- A..<n> - a sequence of Latin letters with a length not exceeding <n>;
- N<n> - a sequence of digits of length <n>;
- N..<n> - a sequence of digits with a length not exceeding <n>;
- AN<n> - a sequence of Latin letters and numbers of fixed length <n>;
- AN..<n> - a sequence of Latin letters and numbers with a length not exceeding <n>;
- ANS<n> - a sequence of Latin letters, numbers and characters of fixed length <n>
- ANS..<n> - a sequence of Latin letters, numbers and characters with a length not exceeding <n>;
- UTC - date and time, in this case: the date must be passed without specifying the time zone, Moscow time, for the SOAP protocol, the standard encoding xs: dateTime is used.

Request parameters

The request parameters are given in table below.

Name	Type	Mandatory	Description
userName	AN..30	Yes	Login of the service account of the merchant.
password	AN..30	Yes	Merchant's service account password.
orderNumber	ANS..32	Yes	Order number in the store system.
language	A2	No	Language in the ISO 639-1 encoding. If the language is not specified, the default language defined in the store settings is used.
bindingId	AN..255	Yes	Identifier of the binding created earlier.
amount	N..12	Yes	Payment amount in minimum currency units.
clientId	ANS..255	Yes	Identifier of the Customer in the Store system. This parameter is used for the binding functionality. May be present if the store is allowed to create bindings. Specifying this parameter when processing payments with the use of bindings is mandatory. Otherwise, a payment will be unsuccessful.
currency	N3	No	ISO 4217 code of the payment currency. If not specified, default value is used.
description	ANS..512	No	Description of the order in free form. To enable sending this field to the processing system, contact the technical support service.

Name	Type	Mandatory	Description
additionalParameters	Not applicable	No	<p>Additional parameters of the order that are stored in the merchant personal account for the subsequent viewing. Each new pair of a parameter name and its value must be separated by a comma. Below is an example of how to use this parameter.</p> <pre>{ "firstParamName": "firstParamValue", "secondParamName": "secondParamValue" }</pre> <p>If the merchant has fiscalization set up, when indicating email (the buyer's email address) and/or phone (the buyer's cell phone number) as additional parameters, these parameters are first used to send the fiscal receipt. It is forbidden to pass reserved names in the parameter (if they are passed, the order may be rejected):</p> <ul style="list-style-type: none"> • sbrf_spasibo:amount_bonus • sbrf_sbermiles:amount_bonus • loyaltyId
billingPayerData	See description	No	Customer's registration data (street address, postal code). Required for AVS/AVV checks. Mandatory if «AVS/AVV use allowed» permission is enabled for merchant

billingPayerData

billingPayerData block parameters

Name	Type	Mandatory	Description
billingCity	AN..50	No	City registered for the card at the Issuer Bank.
billingCountry	AN..50	No	
billingAddressLine1	AN..50	No	Address registered for the card at the Issuer Bank. Line 1. Mandatory if «AVS/AVV use allowed» permission is enabled for merchant.
billingAddressLine2	AN..50	No	Address registered for the card at the Issuer Bank. Line 2.
billingAddressLine3	AN..50	No	Address registered for the card at the Issuer Bank. Line 3.
billingPostalCode	AN..50	No	Postal code registered for the card at the Issuer Bank. Mandatory if «AVS/AVV use allowed» permission is enabled for merchant.
billingState	AN..50	No	State registered for the card at the Issuer Bank (ISO 3166-2).

Response parameters

The response parameters are given in table below.

Name	Type	Mandatory	Description
success	A..5	Yes	Designates a successful request. The following values are available: <ul style="list-style-type: none">• true – request is processed successfully;• false – request failed.
data block (returned only if the request was successful)			
orderId	ANS36	Yes	Identifier of the order in the payment system. It is unique within the system. Missing if order registration failed due to an error detailed in ErrorCode.
error block (returned only if the request resulted in an error)			
code	N3	Yes	Error code.
description	ANS..512	Yes	A detailed technical explanation of the error – the contents of this parameter is not to be displayed to the customer.
message	AN..512	Yes	Comprehensive error description – it is intended for displaying to the user.

Error codes

Error code	Error text
0	The request has been processed without system errors.
1	The funds on the card are not sufficient.
1	Wrong order number.
2	The binding is not found.
4	Invalid binding identifier [bindingId].
5	Using binding is disabled.
5	Invalid amount [amount].
5	Incorrect login.
5	Incorrect password
5	Authentication error
7	System error.
10	An order with this number has already been registered.
10	Incorrect value of [currency]
10	Incorrect value of [language]
10	Duplicate order number
10	Incorrect value of [orderNumber]
10	Incorrect value of [orderDescription]. Links in the order description are not allowed

Examples

Request example

```
{
  "userName": "userName",
  "password": "password",
  "orderNumber": "UAF-203974-DE-12",
  "language": "RU",
  "bindingId": "binding_id",
  "amount": 12300,
  "currency": "810",
  "description": "Test description",
  "additionalParameters": {
    "firstParamName": "firstParamValue",
    "secondParamName": "secondParamValue"
  }
}
```

Example of successful payment

```
{
  "success": true,
  "data": {
    "orderId": "f7beebe4-7c9a-43cf-8e26-67ab741f9b9e"
  },
  "orderStatus": {
    "errorCode": "0",
    "orderNumber": "UAF-203974-DE-12",
    "orderStatus": 2,
    "actionCode": 0,
    "actionCodeDescription": "",
    "amount": 12300,
    "currency": "810",
    "date": 1491333938243,
    "orderDescription": "Test description",
    "merchantOrderParams": [
      {
        "name": "firstParamName",
        "value": "firstParamValue"
      },
      {
        "name": "secondParamName",
        "value": "secondParamValue"
      }
    ],
    "attributes": [],
  }
}
```

```

    "cardAuthInfo": {
      "expiration": "201912",
      "cardholderName": "sdf sdf",
      "approvalCode": "123456",
      "paymentSystem": "VISA",
      "pan": "411111**1111"
    },
    "authDateTime": 1491333939454,
    "terminalId": "11111",
    "authRefNum": "111111111111",
    "paymentAmountInfo": {
      "paymentState": "DEPOSITED",
      "approvedAmount": 12300,
      "depositedAmount": 12300,
      "refundedAmount": 0
    },
    "bankInfo": {
      "bankCountryName": "<UNKNOWN>"
    },
    "chargeback": false,
    "operations": [
      {
        "amount": 12300,
        "cardHolder": "sdf sdf",
        "authCode": "123456"
      }
    ]
  }
}

```

Example of unsuccessful payment

```

{
  "error": {
    "code": "10",
    "description": "An order with this number has already been registered",
    "message": "An order with this number has already been registered."
  },
  "success": false
}

```