

# Request for a binding deactivation (unBindCard.do)

The request used for making an existing binding inactive is `unBindCard.do`.

In this document, the following data type conventions are used when describing request and response parameters:

- A<n> - a sequence of Latin letters of length <n>;
- A..<n> - a sequence of Latin letters with a length not exceeding <n>;
- N<n> - a sequence of digits of length <n>;
- N..<n> - a sequence of digits with a length not exceeding <n>;
- AN<n> - a sequence of Latin letters and numbers of fixed length <n>;
- AN..<n> - a sequence of Latin letters and numbers with a length not exceeding <n>;
- ANS<n> - a sequence of Latin letters, numbers and characters of fixed length <n>
- ANS..<n> - a sequence of Latin letters, numbers and characters with a length not exceeding <n>;
- UTC - date and time, in this case: the date must be passed without specifying the time zone, Moscow time, for the SOAP protocol, the standard encoding `xs:dateTime` is used.

## Request parameters

Name	Type	Mandatory	Description
userName	AN..30	Yes	Login of the service account of the merchant.
password	AN..30	Yes	Merchant's service account password.
bindingId	AN..255	Yes	The identifier of the previously created binding. Can only be used if the merchant has permission to work with bindings. If this parameter is passed in the given request, it means that: 1. The given order can be paid only using a binding; 2. The payer will be redirected to the payment page on which only entering CVC is required.

## Response parameters

Name	Type	Mandatory	Description
errorCode	ANS..3	No	Error code. Can be missing if the result has not caused an error.
errorMessage	AN..512	No	Error description in the language passed in the language parameter in the request.

## Error codes

Error code	Error text
0	The request has been processed without system errors.
2	Wrong binding state. (On an attempt to deactivate an inactive binding.)

Error code	Error text
2	The binding is not found.
5	Access denied.
5	The user must change the password.
7	System error.

## Examples

### POST request example

```
bindingId=fd3afc57-c6d0-4e08-aaef-1b7cfeb093dc
```

### Response example

```
{"errorCode": "2", "errorMessage": "Bundle not found"}
```