

# Request for completion in partial amount, monetary funds, shopping cart (depositOrder)

The request used for debiting the full pre-authorized amount is `depositOrder`. This operation can be performed provided that the merchant has the corresponding permissions in the system.

Use the following URL to connect to the Test Service (WSDL):

<https://3dsec.sberbank.ru/payment/webservices/merchant-ws?wsdl>.

When orders are completed, the cart is passed in the element `depositItems`.

- In the case of completing an order with a full pre-authorized amount, passing the cart data is optional.
- The operation completion amount in the cart must not exceed the pre-authorized amount of the order.
- When completing an order for an amount that differs from the amount of the pre-authorization (apart from passing the 0 value), the data about the cart of items must mandatory be passed.
- Prices of all the items in the cart must be specified in the same currency (if the currency of items is to be specified) and must match the currency of the original order. For Sberbank «Spasibo» the order currency must be Russian rubles (643-RUB).
- It is prohibited to pass in the cart new items, which are missing from the original order. A check is carried out whether given item in the request cart is present in the original order. The `positionId`, `name`, and `itemCode` must match. If at least one value does not coincide, it is considered that the line item is missing from cart in the registration order.
- The value of the `quantity` element in the cart of the completion request must not exceed the value of the same parameter in the cart of the registration order request.
- The `itemAmount` element value of the `items` block must not exceed the value of the same parameter in the original order.
- A passed value of the `quantity` parameter is to be checked for each line item. If the value is too large or too small, the request will fail.
- All the parameters of the cart are to be checked for meeting the required format (length).

If at least one of the above conditions is not met, the order completion request is considered incorrectly formed and the payment gateway returns an error.

In this document, the following data type conventions are used when describing request and response parameters:

- `A<n>` – a sequence of Latin letters of length `<n>`;
- `A..<n>` – a sequence of Latin letters with a length not exceeding `<n>`;
- `N<n>` – a sequence of digits of length `<n>`;
- `N..<n>` – a sequence of digits with a length not exceeding `<n>`;
- `AN<n>` – a sequence of Latin letters and numbers of fixed length `<n>`;
- `AN..<n>` – a sequence of Latin letters and numbers with a length not exceeding `<n>`;
- `ANS<n>` – a sequence of Latin letters, numbers and characters of fixed length `<n>`

- ANS.. <n> - a sequence of Latin letters, numbers and characters with a length not exceeding <n>;
- UTC - date and time, in this case: the date must be passed without specifying the time zone, Moscow time, for the SOAP protocol, the standard encoding xs: dateTime is used.

## Request parameters

Name	Type	Mandatory	Description	FFD version
orderId	ANS36	Yes	Identifier of the order in the payment system. It is unique within the system. The identifier is missing if the order registration failed due to an error detailed in errorCode.	All versions.
depositAmount	N..5	Yes	The amount to be charged in the currency of the order (in minimum currency units). The amount must coincide with the total amount to be charged for all items in the cart for the completion operation. Note: The withdrawal amount is indicated only in money.	All versions.
language	A2	No	Language code in accordance with ISO 639-1. If this parameter is not specified, it is considered that the language is Russian. An error message will be returned in this language.	All versions.
depositItems	Not applicable	Yes	Tag with the attributes of the cart items. Nested tags are described below. ( <a href="#">See description.</a> )	All versions.

### depositItems

depositItems contains the following elements.

A parameter included in a block and indicated as mandatory is only mandatory within that block. If the section is optional and missing, then the parameters included in it should not be passed.

Name	Type	Mandatory	Description	FFD version
items	Not applicable	Yes	An element of the array containing attributes of an item in the cart. The description of the attributes is given below. ( <a href="#">See description.</a> )	All versions.

### items

A parameter included in a block and indicated as mandatory is only mandatory within that block. If the section is optional and missing, then the parameters included in it should not be passed.

Name	Type	Mandatory	Description	FFD version
positionId	ANS..12	Yes	Unique identifier of a line item within the order cart.	All versions.

Name	Type	Mandatory	Description	FFD version
<b>Name</b> name <b>Type</b> ANS..100 <b>Description</b> <b>REST</b> Name or the description of an item in any format. Use - to pass \ use \«- to pass » <b>REST Online Lending</b> For Online Lending functionality, it's necessary to specify a description of the line item in accordance with the Yandex.Market catalog, subject to the following requirements: • <b>The following words and character sequences are not allowed:</b> file, exec, insert, as, select, or, procedure, limit, order, and, or, by, asc, desc, delete, update, distinct, having, truncate, replace, handler, like, regex, tz_offset, to_timestamp_tz, bfilename, union, sql-command, abort, alter, analyze, begin, audit, checkpoint, close, cluster, comment, commit, copy, create, deallocate, declare, delete, drop, end, execute, explain, fetch, grant, insert, lock, move, noaudit, notify, prepare, reindex, rename, reset, revoke, rollback, savepoint, select, set, show, shutdown, start, truncate, unlisten, update, vacuum • <b>The following special characters are not allowed:</b> ' & - # %   ; = <b>WS</b> Name or the description of an item in any format. Use - to pass \ use \«- to pass » <b>WS Online Lending</b> For online crediting functionality it's necessary to specify a description of the good item in accordance with the Yandex.Market.	ANS..100	Yes	Name or the description of an item in any format. Use - to pass \ use \«- to pass »	All versions.
itemDetails	Not applicable	No	Additional block containing the parameters describing a line item. The description of the attributes is given below. The field size limit is 1024 bytes. ( <a href="#">Go to description.</a> )	All versions.
quantity	N..18	Yes	Element describing the total of items of one positionId and its unit of measurement The description of the attributes is given below. ( <a href="#">Go to description.</a> )	All versions.

Name	Type	Mandatory	Description	FFD version
itemAmount	N..18	Yes	The sum of the cost of all line items of one positionId in minimum currency units. Passing itemAmount is mandatory only if the itemPrice parameter was not passed. Otherwise passing of itemAmount is not required. If both parameters - itemPrice and itemAmount - are passed, then itemAmount must be equal to itemPrice * quantity, otherwise, the request will result in an error. When calculating itemAmount = itemPrice*quantity parameter, the result is rounded up to the second digit after the decimal point. For example, if the calculation result is 100.255, then final value will be 100.26.	All versions.
itemCurrency	N3	No	Currency code of a line item according to ISO 4217. If the parameter is not specified, it is considered to be equal to the order currency.	All versions.
itemCode	ANS..100	Yes	Number (identifier) of a line item in the store system.	All versions.
tax	Not applicable	Only if the Merchant is connected to fiscalization service	An additional tag with attributes describing the tax. Nested tags are described below. ( <a href="#">Go to description.</a> )	All versions.
itemPrice	N..18	Only if the Merchant is connected to fiscalization service	The price of one line item of one positionId specified in minimum currency units. Mandatory for merchants using fiscalization. <ul style="list-style-type: none"> <li>itemPrice cannot be less than 0.</li> <li>itemPrice may be either string or integer.</li> </ul>	All versions.
itemAttributes	See description.	Only for stores with enabled fiscalization settings	Tag that serves to pass a set of attributes of the line item. Attributes must be specified as follows. <pre>&lt;attributes name="attribute_name_1"&gt;attribute_value_1&lt;/attributes&gt; &lt;attributes name="attribute_name_2"&gt;attribute_value_2&lt;/attributes&gt;</pre> See description <a href="#">below</a> .	1.05 and later versions.

## itemAttributes

Name	Type	Mandatory	Description	FFD version
paymentMethod	N..2	Yes	<p>Payment type. Possible values:</p> <ul style="list-style-type: none"> <li>• 1 - full pre-payment before the delivery date of the payment subject;</li> <li>• 2 - partial pre-payment before the delivery date of the payment subject;</li> <li>• 3 - advance payment;</li> <li>• 4 - full payment on the delivery date of the payment subject;</li> <li>• 5 - partial payment for the payment subject on the delivery date followed by payment on credit;</li> <li>• 6 - delivery of the payment subject on the delivery date without payment followed by payment on credit;</li> <li>• 7 - payment for the payment subject after its delivery using payment on credit.</li> </ul> <p>Values are passed in the following priority (indicated in descending order of priority):</p> <ol style="list-style-type: none"> <li>1. Shopping cart from API request.</li> <li>2. Fiscalization settings in your personal account.</li> <li>3. Default values.</li> </ol> <p>For paymentMethod, the default value is 1 (full prepayment before the transfer of the payment item).</p>	1.05 and later versions.

Name	Type	Mandatory	Description	FFD version
paymentObject	N..2	Yes	<p>Type of item being paid for. Possible values:</p> <ul style="list-style-type: none"> <li>• 1 - product;</li> <li>• 2 - excisable product;</li> <li>• 3 - work;</li> <li>• 4 - service;</li> <li>• 5 - gambling bet;</li> <li>• 6 - gambling winnings;</li> <li>• 7 - lottery ticket;</li> <li>• 8 - lottery winnings;</li> <li>• 9 - intellectual property;</li> <li>• 10 - payment;</li> <li>• 11 - agent's fee;</li> <li>• 12 - several subjects;</li> <li>• 13 - other payment subject.</li> <li>• * 14 - property rights;</li> <li>• 15 - non-operating income;</li> <li>• 16 - insurance premiums: on the amount of expenses that reduce the amount of tax (advance payments) in accordance with paragraph 3.1 of Article 346.21 of the Tax Code of the Russian Federation;</li> <li>• 17 - sales tax;</li> <li>• 18 - resort tax.</li> </ul> <p>Values are passed in the following priority (indicated in descending order of priority):</p> <ol style="list-style-type: none"> <li>1. Shopping cart from API request.</li> <li>2. Fiscalization settings in your personal account.</li> <li>3. Default values.</li> </ol> <p>The default value for paymentObject is 1 (item).</p>	1.05 and later versions.
nomenclature	ANS	yes (if markQuantity is passed)	Trade item code in text representation. Maximum length - 32 bytes.	1.05 and later versions.
markQuantity ( <a href="#">Go to description.</a> )		No	Fractional quantity of the labeled item.	1.2 and later versions.

Name	Type	Mandatory	Description	FFD version
userData	ANS..64	No	Value of user details. May be transferred only after approval by Federal Tax Service.	1.05 and later versions.
agent_info.type	N..2	Mandatory if agent_info object is passed.	Agent type. The following values are available: <ul style="list-style-type: none"> <li>• 1 – banking payment agent;</li> <li>• 2 – banking payment subagent;</li> <li>• 3 – payment agent;</li> <li>• 4 – payment subagent;</li> <li>• 5 – attorney;</li> <li>• 6 – commission agent;</li> <li>• 7 – other agent.</li> </ul>	1.05 and later versions.
agent_info.paying.operation	ANS..24	No	Name of the transaction of the paying agent.	1.05 and later versions.
agent_info.paying.phones	array ANS..19	No	Phone numbers array of the payments agent in +N format.	1.05 and later versions.
agent_info.paymentsOperator.phones	Array ANS..19	No	Phone numbers array of the payments operator in +N format.	1.05 and later versions.
agent_info.MTOperator.phones	array ANS..19	No	An array of Money Transfer operator phone numbers in +N format.	1.05 and later versions.
agent_info.MTOperator.name	ANS..64	No	Money Transfer operator name.	1.05 and later versions.
agent_info.MTOperator.address	ANS..256	No	Money Transfer operator address.	1.05 and later versions.
agent_info.MTOperator.inn	N10..12	No	Money Transfer operator TIN.	1.05 and later versions.
supplier_info.phones	Array ANS..19	No	An array of supplier phone numbers in +N format.	1.05 and later versions.
supplier_info.name	ANS..256	No	Supplier name.	1.05 and later versions.
supplier_info.inn	N10..12	No	Supplier TIN.	1.05 and later versions.

## quantity

quantity contains the following elements.

Name	Type	Mandatory	Description	FFD version
measure	ANS..20	Yes	The unit of measurement for the quantity of line item instances.	All versions.

If the FFD is version 1.2 or later, then the following parameters are passed here:

Name	Type	Mandatory	Description	FFD version
value	N1	Yes	Quantity of line items in given positionId. For FFD version 1.2+, the value is always 1.	1.2 and later versions.

Name	Type	Mandatory	Description	FFD version
measure	N..3	Yes	Unit of measurement for the quantity of the payment subject. In case of FFD version 1.2+, if the 'nomenclature' and 'markQuantity' parameters are passed, the value is always 0. In other cases, it can have some value.	1.2 and later versions.

Possible values of **measure**

Value	Description
0	Used for payment subjects that can be sold individually or in units (as well as in the event that the payment subject is a product subject to mandatory labeling with an identification tool (which can be known from mark_code being passed))
10	Gram
11	Kilogram
12	Ton
20	Centimeter
21	Decimeter
22	Meter
30	Square centimeter
31	Square decimeter
32	Square meter
40	Milliliter
41	Liter
42	Cubic meter
50	Kilowatt hour
51	Gigacalorie
70	Day (24h)
71	Hour
72	Minute
73	Second
80	Kilobyte
81	Megabyte
82	Gigabyte
83	Terabyte
255	Applicable when using other units of measurement

## markQuantity

Parameters of **markQuantity** tag:

*A parameter included in a tag and indicated as mandatory is only mandatory within that tag. If the tag itself is not mandatory and is not passed, its included parameters should not be passed.*

Name	Type	Mandatory	Description
numerator	N..12	yes	The numerator of the fractional part of the payment subject.
denominator	N..12	yes	The denominator of the fractional part of the payment subject.



itemDetails

'itemDetails contains the following elements.

A parameter included in a block and indicated as mandatory is only mandatory within that block. If the section is optional and missing, then the parameters included in it should not be passed.

Name	Type	Mandatory	Description	FFD version
itemDetailsParams	ANS..255	No	Parameter describing additional information regarding a line item. The description of the attributes is given below. ( <a href="#">Go to description.</a> )	All versions.

==== itemDetailsParams ==== 'itemDetailsParams contains the following elements.

Name	Type	Mandatory	Description	FFD version
<b>Name</b> name <b>Type</b> AN..255 <b>Type2</b> ANS..255 <b>Description</b> <b>REST</b> Name of the parameter describing the details of a line item <b>WS</b> Name of the parameter describing the details of a line item	AN..255	Yes	Name of the parameter describing the details of a line item	All versions.

tax

tax contains the following elements.

A parameter included in a block and indicated as mandatory is only mandatory within that block. If the section is optional and missing, then the parameters included in it should not be passed.

Name	Type	Mandatory	Description	FFD version
taxType	N..2	Yes	VAT rate. The following values are available: <ul style="list-style-type: none"> <li>• 0 – without VAT;</li> <li>• 1 – VAT at rate of 0%;</li> <li>• 2 – receipt VAT at rate of 10%;</li> <li>• 4 – receipt VAT at calculated rate of 10/110;</li> <li>• 6 – receipt VAT at rate of 20%;</li> <li>• 7 – receipt VAT at calculated rate of 20/120.</li> </ul> If the cart and fiscalization data are not included in the request, then the default values specified in the personal account are passed to the Fiscal Data Operator (see User Manual for personal account).	All versions.
taxSum	N..18	Yes	Amount of the tax calculated by the merchant. The amount is specified in minimum currency units	All versions.

## Response parameters

Name	Type	Mandatory	Description	FFD version
errorCode	N3	Yes	Error code.	All versions.
errorMessage	AN..512	No	Error description in the language passed in the language parameter in the request.	All versions.

## Error codes

Value	Description
0	The request has been processed without system errors.
5	The deposit amount must be equal to zero or not less than one ruble.
5	Access denied.
5	The user must change the password.
6	Wrong order number.
6	[orderId] is empty.
7	Payment must be in the correct state.
7	System error.
8	The deposit amount exceeds the amount on order registration.
8	[depositItems.items.currency] the currency in the cart does not match the order currency.
8	[depositItems.totalAmount] the sum of items in the cart does not match the total.
8	[items.item.position] the original order does not contain a heading with this number.
8	[refundItems.item.quantity.value] Too high or too low value.

## Examples

## Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header/>
  <soapenv:Body>
    <mer:depositOrder>
      <order language="ru" orderId="76d7885f-562a-4bac-abc3-18ecaaaca797"
depositAmount="20777">
        <!--Optional:-->
        <depositItems>

          <!--Zero or more repetitions:-->
          <items positionId="1">
            <name>Metzeler Enduro 3 Sahara</name>
            <!-- Optional: -->
            <itemDetails>
              <!-- Zero or more repetitions: -->
              <itemDetailsParams
name="brand">Metzeler</itemDetailsParams>
              <itemDetailsParams
name="radius">17inch</itemDetailsParams>
            </itemDetails>
            <quantity measure="pieces">1</quantity>
            <itemAmount>7777</itemAmount>
            <itemCurrency>643</itemCurrency>
            <itemCode>T-M-14</itemCode>
            <tax>
              <taxType>1</taxType>
              <taxSum>111</taxSum>
            </tax>
            <itemPrice>7777</itemPrice>
          </items>

          <items positionId="2">
            <name>Universal Mirror Enduro</name>
            <!-- Optional: -->
            <itemDetails>
              <!-- Zero or more repetitions: -->
              <itemDetailsParams
name="brand">Noname</itemDetailsParams>
              <itemDetailsParams
name="diameter">12mm</itemDetailsParams>
            </itemDetails>
            <quantity measure="pieces">1</quantity>
            <itemAmount>5000</itemAmount>
            <itemCurrency>643</itemCurrency>
            <itemCode>NM-15</itemCode>
```

```

        <tax>
            <taxType>1</taxType>
            <taxSum>111</taxSum>
        </tax>
        <itemPrice>5000</itemPrice>
    </items>

    <items positionId="3">
        <name>Warm Grips</name>
        <!-- Optional: -->
        <itemDetails>
            <!-- Zero or more repetitions: -->
            <itemDetailsParams
name="brand">Noname</itemDetailsParams>
        </itemDetails>
        <quantity measure="pieces">1</quantity>
        <itemAmount>8000</itemAmount>
        <itemCurrency>643</itemCurrency>
        <itemCode>G-16</itemCode>
        <tax>
            <taxType>1</taxType>
            <taxSum>111</taxSum>
        </tax>
        <itemPrice>8000</itemPrice>
    </items>

</depositItems>

    <!--Zero or more repetitions:-->
    <params name=" " value=" " />
</order>

</mer:depositOrder>
</soapenv:Body>
</soapenv:Envelope>

```

## Пример ответа

```

<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
    <soap:Body>
        <ns1:depositOrderResponse
xmlns:ns1="http://engine.paymentgate.ru/webservices/merchant">
            <return errorCode="0"/>
        </ns1:depositOrderResponse>
    </soap:Body>
</soap:Envelope>

```