

Request for changing the validity period of a binding (extendBinding)

Use the extendBinding method to change the validity period of a binding.

Use the following URL to connect to the Test Service (WSDL):

<https://3dsec.sberbank.ru/payment/webservices/merchant-ws?wsdl>.

In this document, the following data type conventions are used when describing request and response parameters:

- A<n> - a sequence of Latin letters of length <n>;
- A..<n> - a sequence of Latin letters with a length not exceeding <n>;
- N<n> - a sequence of digits of length <n>;
- N..<n> - a sequence of digits with a length not exceeding <n>;
- AN<n> - a sequence of Latin letters and numbers of fixed length <n>;
- AN..<n> - a sequence of Latin letters and numbers with a length not exceeding <n>;
- ANS<n> - a sequence of Latin letters, numbers and characters of fixed length <n>
- ANS..<n> - a sequence of Latin letters, numbers and characters with a length not exceeding <n>;
- UTC - date and time, in this case: the date must be passed without specifying the time zone, Moscow time, for the SOAP protocol, the standard encoding xs: dateTime is used.

Request parameters

Name	Type	Mandatory	Description
bindingId	AN..255	Yes	The identifier of the previously created binding. Can only be used if the merchant has permission to work with bindings. If this parameter is passed in the given request, it means that: 1. The given order can be paid only using a binding; 2. The payer will be redirected to the payment page on which only entering CVC is required.
newExpiry	N6	Yes	New expiration date (year and month) in the format YYYYDD .
language	A2	No	Language in the ISO 639-1 encoding. If the language is not specified, the default language defined in the store settings is used.

Response parameters

Name	Type	Mandatory	Description
errorCode	ANS..3	No	Error code.
errorMessage	AN..512	(on an error)	Error description in the language passed in the language parameter in the request.

Error codes

Error code	Error text
0	The request has been processed without system errors.
2	The binding is not found.
5	Access denied.
5	The user must change the password.
7	System error.

Examples

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header/>
  <soapenv:Body>
    <mer:extendBinding>
      <request language=" " bindingId="1eabfb8e-b90e-4dc8-
bef6-14bd392b1cec" newExpiry="201807"/>
    </mer:extendBinding>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:extendBindingResponse
xmlns:ns1="http://engine.paymentgate.ru/webservices/merchant">
      <return errorCode="0" errorMessage="Successful"/>
    </ns1:extendBindingResponse>
  </soap:Body>
</soap:Envelope>
```