

Request for payment using Google Pay with fiscal data (googlePay)

The request used for payment via Google Pay is googlePay.

Use the following URL to connect to the Test Service (WSDL):

<https://3dsec.sberbank.ru/payment/webservices/merchant-ws?wsdl>.

Use the standard requests to the payment gateway for the operations of reversal, refund and payment completion.

In this document, the following data type conventions are used when describing request and response parameters:

- A<n> - a sequence of Latin letters of length <n>;
- A..<n> - a sequence of Latin letters with a length not exceeding <n>;
- N<n> - a sequence of digits of length <n>;
- N..<n> - a sequence of digits with a length not exceeding <n>;
- AN<n> - a sequence of Latin letters and numbers of fixed length <n>;
- AN.. <n> - a sequence of Latin letters and numbers with a length not exceeding <n>;
- ANS<n> - a sequence of Latin letters, numbers and characters of fixed length <n>
- ANS.. <n> - a sequence of Latin letters, numbers and characters with a length not exceeding <n>;
- UTC - date and time, in this case: the date must be passed without specifying the time zone, Moscow time, for the SOAP protocol, the standard encoding xs:dateTime is used.

Request parameters

The request parameters are given in table below.

Name	Type	Mandatory	Description
merchant	AN..255	Yes	Merchant login in the payment gateway.
orderNumber	ANS..32	Yes	The number (identifier) of the order in the store system is unique for each store within the system - up to 30 characters. If the order number is generated on the Payment Gateway side, this parameter is not mandatory.
paymentToken	AN..8192	Yes	A token obtained from Google Pay and encoded in Base64.
ip	ANS..39	No	IP-address of the buyer. IPv6 is supported in all requests (up to 39 characters).
amount	N..12	No	Payment amount in minimum currency units.
description	ANS..598	No	Description of the order in any format. Only the first 24 characters of this field are transferred to Sberbank's processing for inclusion in the merchant's financial statements. To enable sending this field to the processing system, contact the technical support service.

Name	Type	Mandatory	Description									
language	A2	No	Language in the ISO 639-1 encoding. If the language is not specified, the default language defined in the store settings is used.									
additionalParameters	Not applicable	No	<p>Additional parameters of the order that are stored in the merchant personal account for the subsequent viewing. For each additional parameter, use the entry block which includes the following nested parameters.</p> <table border="1"> <thead> <tr> <th>Name</th><th>Type</th><th>Description</th></tr> </thead> <tbody> <tr> <td>key</td><td>String</td><td>The name of the optional parameter.</td></tr> <tr> <td>value</td><td>AN..1024</td><td>The value of the additional parameter is up to 1024 characters.</td></tr> </tbody> </table> <p>Below is an example of how to use this parameter.</p> <pre><entry> <key>parameter_1</key> <value>value_1</value> </entry> <entry> <key>parameter_2</key> <value>value_2</value> </entry></pre> <p>If the merchant has fiscalization set up, when indicating email (the buyer's email address) and/or phone (the buyer's cell phone number) as additional parameters, these parameters are first used to send the fiscal receipt.</p> <p>It is forbidden to pass reserved names in the parameter (if they are passed, the order may be rejected):</p> <ul style="list-style-type: none"> • sbrf_spasibo:amount_bonus • sbrf_sbermiles:amount_bonus 	Name	Type	Description	key	String	The name of the optional parameter.	value	AN..1024	The value of the additional parameter is up to 1024 characters.
Name	Type	Description										
key	String	The name of the optional parameter.										
value	AN..1024	The value of the additional parameter is up to 1024 characters.										
preAuth	A..5	No	<p>Parameter that defines the necessity of a pre-authorization (locking the amount on hold on the customer's account until its debiting). The following values are available:</p> <ul style="list-style-type: none"> • true - the parameter is enabled, a two-phase payment is made; • false - the parameter is disabled, a one-phase payment is made (funds are debited immediately). <p>If the parameter is not specified in the request, a one-phase payment occurs.</p> <p>Two-phase payments functionality is available if specifically requested by Merchant from the bank.</p> <p>This parameter can be passed either as a boolean value (without quotation marks) or as a string (with quotation marks).</p>									
clientId	ANS..255	No	<p>Identifier of the Customer in the Store system. This parameter is used for the binding functionality. May be present if the store is allowed to create bindings.</p> <p>Specifying this parameter when processing payments with the use of bindings is mandatory. Otherwise, a payment will be unsuccessful.</p>									
currencyCode	N3	No	Numeric ISO 4217 code of the payment currency. If this parameter is not specified, it is considered to be equal to the default currency code.									
email	ANS..40	No	Customer's email address. You can specify several comma separated (without spaces) email addresses - in this case the receipt will be delivered to all specified addresses.									

Name	Type	Mandatory	Description
phone	NS..12	No	<p>Customer's phone number. It can be of the following format: $^{((+7 8)?([0-9])\{10\})\\$}$. Examples:</p> <ul style="list-style-type: none"> • +79000000000 • 89000000000 • 9000000000 • 79000000000 <p>If the number is passed in a separate parameter and in additional parameters, the number specified in this phone parameter will be used.</p>
returnUrl	ANS..512	Yes	<p>The URL to which the user is to be redirected in case of a successful payment (and also in case of a failed payment where the failUrl parameter is not passed). The address must be specified in full including the protocol used (for example, https://test.ru instead of test.ru). Otherwise, the user will be redirected to the address of the following type: http://<payment_gateway_address>/<merchant_address>.</p>
failUrl	ANS..512	No	<p>The address to which the user is to be redirected in case of a failed payment. The address must be specified in full including the protocol used (for example, https://test.ru instead of test.ru). Otherwise, the user will be redirected to the address of the following type: http://<payment_gateway_address>/<merchant_address>. The parameter is optional. In this case, an unsuccessful payment will lead to a redirect to returnUrl, in the same way it happens when the payment is successful.</p>
additionalOfdParams	Data block for transferring additional parameters of the OFD	Yes	<p>Some parameters of additionalOfdParams block duplicate parameters of cartItems.items.itemAttributes block. The additionalOfdParams block is included for all line items of the order, whereas cartItems.items.itemAttributes applies to individual items. If the additionalOfdParams and cartItems.items.itemAttributes and additionalOfdParams blocks pass different values, then the priority value will be the one that was passed in cartItems.items.itemAttributes, that is, for an individual position.</p> <p>The transfer of this block is possible only when using the following OFDs:</p> <ul style="list-style-type: none"> • ATOL; • Business.Ru; • Evotor. <p>(Go to description.)</p>
orderBundle	Not applicable	Yes	<p>Block containing the cart of items of the order. The description of the attributes is given below.</p> <p>(Go to description.)</p>

orderBundle

orderBundle contains the following elements.

A parameter included in a block and indicated as mandatory is only mandatory within that block. If the section is optional and missing, then the parameters included in it should not be passed.

Name	Type	Mandatory	Description	FFD version
orderCreationDate	ANS..21	No	Order creation date in the format YYYY-MM-DDTHH:MM:SS.	All versions.
customerDetails	Not applicable	No	Block containing attributes with data about the customer. The description of the attributes is given below. (Go to description.)	All versions.
cartItems	Not applicable	Yes	Block with the attributes of the items in the cart. The description of the attributes is given below. (Go to description.)	All versions.

customerDetails

customerDetails contains the following elements.

A parameter included in a block and indicated as mandatory is only mandatory within that block. If the section is optional and missing, then the parameters included in it should not be passed.

Name	Type	Mandatory	Description	FFD version
email	ANS..40	See note below.	Customer's email address. You can specify several comma separated (without spaces) email addresses – in this case the receipt will be delivered to all specified addresses.	All versions.

Name	Type	Mandatory	Description	FFD version
phone	NS..12	See note below.	<p>Customer's phone number. It can be of the following format: $^((+7 8)?([0-9])\{10\})\$. Examples:</p> <ul style="list-style-type: none"> • +79000000000 • 89000000000 • 9000000000 • 79000000000 <p>If the number is passed in a separate parameter and in additional parameters, the number specified in this phone parameter will be used.</p> <p>When using ATOL fiscalization, the phone parameter should be sent in the following format:</p> <p>The phone number must be passed together with the country code without spaces and additional characters except for the quotation marks (the number «371 2 1234567» must be passed as «+37121234567»). If the phone number belongs to Russia (prefix «+7»), then the value can be passed without a prefix (the number «+79251234567» can be sent as «9251234567»). The maximum string length is 64 characters. One of the fields must be filled in the request: email or phone.</p>	All versions.
contact	ANS..40	No	Customer's preferred way of communication.	All versions.
deliveryInfo	Not applicable	No	Block containing the attributes of the delivery address. The description of the attributes is given below. (Go to description.)	All versions.
fullName	ANS..100	No	Payer's first name, last name, and patronymic.	1.05 and later versions.
passport	ANS..100	No	The series and number of the payer's passport in the following format: 2222888888.	1.05 and later versions.
inn	N..12	No	Taxpayer identification number. From 10 to 12 digits can be passed.	1.05 and later versions.

It is mandatory to pass one of the two parameters: email or phone.

deliveryInfo

deliveryInfo contains the following elements.

Name	Type	Mandatory	Description	FFD version
deliveryType	ANS..20	No	Delivery method.	All versions.
country	A..2	Yes	The two-letter country code for the delivery country.	All versions.
city	ANS..40	Yes	Delivery city.	All versions.
postAddress	ANS..255	Yes	Delivery address.	All versions.

A parameter included in a block and indicated as mandatory is only mandatory within that block. If the section is optional and missing, then the parameters included in it should not be passed.

cartItems

cartItems contains the following elements.

A parameter included in a block and indicated as mandatory is only mandatory within that block. If the section is optional and missing, then the parameters included in it should not be passed.

Name	Type	Mandatory	Description	FFD version
items	Not applicable	Yes	Tag containing the parameters with the data about one item from the cart . Item number is specified as an attribute of the tag: positionId - Unique identifier of a product item inside the order cart. A request must contain a separate items tag for each line item. The description of the tag parameters is given below. (Go to description.)	All versions.

items

items« contains the following elements.

Name	Type	Mandatory	Description	FFD version
Name name Type ANS..100 Description REST Name or the description of an item in any format. Use - to pass \ use \<- to pass » REST Online Lending For Online Lending functionality, it's necessary to specify a description of the line item in accordance with the Yandex.Market catalog, subject to the following requirements: • The following words and character sequences are not allowed: file, exec, insert, as, select, or, procedure, limit, order, and, or, by, asc, desc, delete, update, distinct, having, truncate, replace, handler, like, regex, tz_offset, to_timestamp tz, bfilename, union, sql-command, abort, alter, analyze, begin, audit, checkpoint, close, cluster, comment, commit, copy, create, deallocate, declare, delete, drop, end, execute, explain, fetch, grant, insert, lock, move, noaudit, notify, prepare, reindex, rename, reset, revoke, rollback, savepoint, select, set, show, shutdown, start, truncate, unlisten, update, vacuum • The following special characters are not allowed: ' & - # % ; = WS Name or the description of an item in any format. Use - to pass \ use \<- to pass » WS Online Lending For online crediting functionality it's necessary to specify a description of the good item in accordance with the Yandex.Market.	ANS..100	Yes	Name or the description of an item in any format. Use - to pass \ use \<- to pass »	All versions.
itemDetails	Not applicable	No	Additional block containing the parameters describing a line item. The description of the attributes is given below. The field size limit is 1024 bytes. (Go to description.)	All versions.
quantity	N..18	Yes	Element describing the total of items of one positionId and its unit of measurement The description of the attributes is given below. (Go to description.)	All versions.

Name	Type	Mandatory	Description	FFD version
itemAmount	N..12	No	The sum of the cost of all line items of one positionId in minimum currency units. Passing itemAmount is mandatory only if the itemPrice parameter was not passed. Otherwise passing of itemAmount is not required. If both parameters – itemPrice and itemAmount – are passed, then itemAmount must be equal to itemPrice * quantity, otherwise, the request will result in an error. When calculating itemAmount = itemPrice*quantity parameter, the result is rounded up to the second digit after the decimal point. For example, if the calculation result is 100.255, then final value will be 100.26.	All versions.
itemCurrency	N3	No	Currency code of a line item according to ISO 4217. If the parameter is not specified, it is considered to be equal to the order currency.	All versions.
itemCode	ANS..100	Yes	Number (identifier) of a line item in the store system.	All versions.
tax	Not applicable	Only for stores with enabled fiscalization settings	An additional tag with attributes describing the tax. Nested tags are described below. (Go to description.)	All versions.
itemPrice	N..18	Only for stores with enabled fiscalization settings	The price of one line item of one positionId specified in minimum currency units. Mandatory for merchants using fiscalization. <ul style="list-style-type: none"> • itemPrice cannot be less than 0. • itemPrice may be either string or integer. 	All versions.
itemAttributes	See description.	Only for stores with enabled fiscalization settings	Tag that serves to pass a set of attributes of the line item. Attributes must be specified as follows. <pre><attributes name="attribute_name_1">attribute_value_1</attributes> <attributes name="attribute_name_2">attribute_value_2</attributes></pre> See description below .	1.05 and later versions.

==== itemAttributes ====
itemAttributes contains the attributes array in which the attributes of a line item must be specified (see example and table below).

<sxh JavaScript>

```
«itemAttributes»:{«attributes»:[{«name»:«paymentMethod»,»value«:<1>},{«name»:«paymentObject»,»value«:<1>}]} </sxh>
```

Name	Type	Mandatory	Description	FFD version
paymentMethod	N..2	Yes	<p>Payment type. Possible values:</p> <ul style="list-style-type: none"> • 1 – full pre-payment before the delivery date of the payment subject; • 2 – partial pre-payment before the delivery date of the payment subject; • 3 – advance payment; • 4 – full payment on the delivery date of the payment subject; • 5 – partial payment for the payment subject on the delivery date followed by payment on credit; • 6 – delivery of the payment subject on the delivery date without payment followed by payment on credit; • 7 – payment for the payment subject after its delivery using payment on credit. <p>Values are passed in the following priority (indicated in descending order of priority):</p> <ol style="list-style-type: none"> 1. Shopping cart from API request. 2. Fiscalization settings in your personal account. 3. Default values. <p>For paymentMethod, the default value is 1 (full prepayment before the transfer of the payment item).</p>	1.05 and later versions.

Name	Type	Mandatory	Description	FFD version
paymentObject	N..2	Yes	<p>Type of item being paid for. Possible values:</p> <ul style="list-style-type: none"> • 1 - product; • 2 - excisable product; • 3 - work; • 4 - service; • 5 - gambling bet; • 6 - gambling winnings; • 7 - lottery ticket; • 8 - lottery winnings; • 9 - intellectual property; • 10 - payment; • 11 - agent's fee; • 12 - several subjects; • 13 - other payment subject. • * 14 - property rights; • 15 - non-operating income; • 16 - insurance premiums: on the amount of expenses that reduce the amount of tax (advance payments) in accordance with paragraph 3.1 of Article 346.21 of the Tax Code of the Russian Federation; • 17 - sales tax; • 18 - resort tax. <p>Values are passed in the following priority (indicated in descending order of priority):</p> <ol style="list-style-type: none"> 1. Shopping cart from API request. 2. Fiscalization settings in your personal account. 3. Default values. <p>The default value for paymentObject is 1 (item).</p>	1.05 and later versions.
nomenclature	ANS	yes (if markQuantity is passed)	Trade item code in text representation. Maximum length – 32 bytes.	1.05 and later versions.
markQuantity (Go to description.)		No	Fractional quantity of the labeled item.	1.2 and later versions.

Name	Type	Mandatory	Description	FFD version
userData	ANS..64	No	Value of user details. May be transferred only after approval by Federal Tax Service.	1.05 and later versions.
agent_info.type	N..2	Mandatory if agent_info object is passed.	Agent type. The following values are available: • 1 - banking payment agent; • 2 - banking payment subagent; • 3 - payment agent; • 4 - payment subagent; • 5 - attorney; • 6 - commission agent; • 7 - other agent.	1.05 and later versions.
agent_info.paying.operation	ANS..24	No	Name of the transaction of the paying agent.	1.05 and later versions.
agent_info.paying.phones	array ANS..19	No	Phone numbers array of the payments agent in +N format.	1.05 and later versions.
agent_info.paymentsOperator.phones	Array ANS..19	No	Phone numbers array of the payments operator in +N format.	1.05 and later versions.
agent_info.MT0operator.phones	array ANS..19	No	An array of Money Transfer operator phone numbers in +N format.	1.05 and later versions.
agent_info.MT0operator.name	ANS..64	No	Money Transfer operator name.	1.05 and later versions.
agent_info.MT0operator.address	ANS..256	No	Money Transfer operator address.	1.05 and later versions.
agent_info.MT0operator.inn	N10..12	No	Money Transfer operator TIN.	1.05 and later versions.
supplier_info.phones	Array ANS..19	No	An array of supplier phone numbers in +N format.	1.05 and later versions.
supplier_info.name	ANS..256	No	Supplier name.	1.05 and later versions.
supplier_info.inn	N10..12	No	Supplier TIN.	1.05 and later versions.

==== quantity ===== quantity contains the following elements.

Name	Type	Mandatory	Description	FFD version
measure	ANS..20	Yes	The unit of measurement for the quantity of line item instances.	All versions.

If the FFD is version 1.2 or later, then the following parameters are passed here:

Name	Type	Mandatory	Description	FFD version
value	N1	Yes	Quantity of line items in given positionId. For FFD version 1.2+, the value is always 1.	1.2 and later versions.

Name	Type	Mandatory	Description	FFD version
measure	N..3	Yes	Unit of measurement for the quantity of the payment subject. In case of FFD version 1.2+, if the 'nomenclature' and 'markQuantity' parameters are passed, the value is always 0. In other cases, it can have some value.	1.2 and later versions.

Possible values of **measure**

Value	Description
0	Used for payment subjects that can be sold individually or in units (as well as in the event that the payment subject is a product subject to mandatory labeling with an identification tool (which can be known from <code>mark_code</code> being passed))
10	Gram
11	Kilogram
12	Ton
20	Centimeter
21	Decimeter
22	Meter
30	Square centimeter
31	Square decimeter
32	Square meter
40	Milliliter
41	Liter
42	Cubic meter
50	Kilowatt hour
51	Gigacalorie
70	Day (24h)
71	Hour
72	Minute
73	Second
80	Kilobyte
81	Megabyte
82	Gigabyte
83	Terabyte
255	Applicable when using other units of measurement

===== markQuantity =====

Parameters of **markQuantity** tag:

A parameter included in a tag and indicated as mandatory is only mandatory within that tag. If the tag itself is not mandatory and is not passed, its included parameters should not be passed.

Name	Type	Mandatory	Description
numerator	N..12	yes	The numerator of the fractional part of the payment subject.
denominator	N..12	yes	The denominator of the fractional part of the payment subject.

==== itemDetails ====
itemDetails contains the following elements.

A parameter included in a block and indicated as mandatory is only mandatory within that block. If the section is optional and missing, then the parameters included in it should not be passed.

Name	Type	Mandatory	Description	FFD version
itemDetailsParams	ANS..255	Yes	Parameter describing additional information regarding a line item. The description of the attributes is given below. (Go to description.)	All versions.

itemDetailsParams

'itemDetailsParams contains the following elements.

Name	Type	Mandatory	Description	FFD version
Name name Type AN..255 Type2 ANS..255 Description REST Name of the parameter describing the details of a line item WS Name of the parameter describing the details of a line item	AN..255	Conditional. Mandatory if itemDetailsParams parameter is present.	Name of the parameter describing the details of a line item	All versions.

==== tax ====
tax contains the following elements.

A parameter included in a block and indicated as mandatory is only mandatory within that block. If the section is optional and missing, then the parameters included in it should not be passed.

Name	Type	Mandatory	Description	FFD version
taxType	N..2	No	VAT rate. The following values are available: • 0 – without VAT; • 1 – VAT at rate of 0%; • 2 – receipt VAT at rate of 10%; • 4 – receipt VAT at calculated rate of 10/110; • 6 – receipt VAT at rate of 20%; • 7 – receipt VAT at calculated rate of 20/120. If the cart and fiscalization data are not included in the request, then the default values specified in the personal account are passed to the Fiscal Data Operator (see User Manual for personal account).	All versions.
taxSum	N..18	No	Amount of the tax calculated by the merchant. The amount is specified in minimum currency units	All versions.

===== additionalOfdParams ===== additionalOfdParams contains the following elements.

Name	Type	Mandatory	Description	FFD version
agent_info.type	N..2	Mandatory if agent_info object is passed.	Agent type. The following values are available: • 1 – banking payment agent; • 2 – banking payment subagent; • 3 – payment agent; • 4 – payment subagent; • 5 – attorney; • 6 – commission agent; • 7 – other agent.	1.05 and later versions.
agent_info.paying.operation	ANS..24	No	Name of the transaction of the paying agent.	1.05 and later versions.
agent_info.paying.phones	array ANS..19	No	Phone numbers array of the payments agent in +N format.	1.05 and later versions.

Name	Type	Mandatory	Description	FFD version
agent_info.paymentsOperator.phones	Array ANS..19	No	Phone numbers array of the payments operator in +N format.	1.05 and later versions.
agent_info.MT0operator.address	ANS..256	No	Money Transfer operator address.	1.05 and later versions.
agent_info.MT0operator.inn	N10..12	No	Money Transfer operator TIN.	1.05 and later versions.
agent_info.MT0operator.name	ANS..64	No	Money Transfer operator name.	1.05 and later versions.
agent_info.MT0operator.phones	array ANS..19	No	An array of Money Transfer operator phone numbers in +N format.	1.05 and later versions.
supplier_info.phones	Array ANS..19	No	An array of supplier phone numbers in +N format.	1.05 and later versions.
cashier	A..256	No	Cashier full name	1.05 and later versions.
additional_check_props	ANS..16	No	Additional property of the receipt.	1.05 and later versions.
additional_user_props.name	ANS..24	No	Name of the additional property of the user.	1.05 and later versions.
additional_user_props.value	ANS..24	No	Value of the additional property of the user.	1.05 and later versions.
cashier_inn	N..12	No	Cashier's INN	1.2 and later versions.
client.address	ANS..256	No	Customer address.	1.2 and later versions.
client.birth_date	NS10	No	Customer birth date as dd.mm.yyyy	1.2 and later versions.
client.citizenship	N3	No	Country numeric code of the county of Customer's citizenship. The country code is specified according to All-Russian World Countries Classifier (OKSM)	1.2 and later versions.

Name	Type	Mandatory	Description	FFD version
client.document_code	N2	No	Identification document type numeric code (for example, 21 stands for Russian Passport).	1.2 and later versions.
client.passport_number	NS11	No	Series and number of the payer's passport: 1111 222222	1.2 and later versions.
client.email	ANS..64	No	Customer's email address. Exactly one of the two fields must be passed: email or phone.	1.2 and later versions.
client.phone	NS..19	No	Customer's phone number. Must be passed with the country code without spaces and additional characters (except for + character). For example, the number «+371 2 1234567» should be passed as «+37121234567»). Exactly one of the two fields must be passed: email or phone.	1.2 and later versions.
client.inn	N12	No	INN of the buyer.	1.2 and later versions.
client.name	ANS..256	No	Customer name.	1.2 and later versions.
operatingCheckProps.name	ANS	No	Operation ID The value is «0» until the value of Russia's Federal Tax Service attribute is determined.	1.2 and later versions.
operatingCheckProps.name	ANS	No	Operation ID The value is «0» until the value of Russia's Federal Tax Service attribute is determined.	1.2 and later versions.

Name	Type	Mandatory	Description	FFD version
operatingCheckProps.timestamp	NS19	No	Date and time of the operation in dd.mm.yyyy HH:MM:SS format	1.2 and later versions.
operatingCheckProps.value	ANS..64	No	Operation data.	1.2 and later versions.
sectoralCheckProps.date	NS10	No	Date of the legislative act of the federal body of executive power that sets forth the requirements for assigning the value of «sectoral attribute». Format: dd.mm.yyyy.	1.2 and later versions.
sectoralCheckProps.federalId	ANS	No	Identifier of federal body of executive power. Must be one of the values from directory of federal bodies of executive power	1.2 and later versions.
sectoralCheckProps.number	N..32	No	Number of the legislative act of the federal body of executive power that sets forth the requirements for assigning the value of «sectoral attribute».	1.2 and later versions.
sectoralCheckProps.value	ANS..256	No	A set of values defined by the legislative act of the federal body of executive power.	1.2 and later versions.

===== Response parameters ===== The response parameters are given in table below.

Name	Type	Mandatory	Description
success	A..5	Yes	Designates a successful request. The following values are available: <ul style="list-style-type: none"> • true – request is processed successfully; • false – request failed.
data block (returned only if the request was successful)			

Name	Type	Mandatory	Description
orderId	ANS36	Yes	Identifier of the order in the payment system. It is unique within the system. The identifier is missing if the order registration failed due to an error detailed in errorCode.
termUrl	AN..512	Only if additional authentication is used on the issuing bank's ACS	URL to redirect the payer to after authentication.
acsUrl	AN..512	Only if additional authentication is used on the issuing bank's ACS	Redirect address to the address of the ACS server.
paReq	AN..512	Only if additional authentication is used on the issuing bank's ACS	Request for the payer authentication.
bindingId	AN..255	The parameter is returned if the bindings are used	Identifier of the binding created earlier.
error block (returned only if the request resulted in an error)			
code	N3	Yes	Error code.
description	ANS..512	Yes	A detailed technical explanation of the error - the contents of this parameter is not to be displayed to the customer.
message	AN..512	Yes	Comprehensive error description - it is intended for displaying to the user.

===== Error codes =====

Error code	Error text
0	The request has been processed without system errors.
5	Access denied.
5	The user must change the password.
7	System error.
10	Invalid parameter value [paymentToken].
10	Invalid parameter value [orderNumber].
10	Invalid parameter value [merchant].
10	Invalid parameter value [ip].
10	Encryption of the data passed in unsuccessful.

===== Request example =====

```

<sxh xml> <soapenv:Envelope
xmlns:soapenv=<a href="http://schemas.xmlsoap.org/soap/envelope/"></a>
xmlns:mer=<a href="http://engine.paymentgate.ru/webservices/merchant"></a>> </soapenv:Header>
<soapenv:Body> <mer:googlePay> <arg0> <additionalParameters/>
<orderNumber>9eac9d14-4430-7e2a-a582-2d3b00096352</orderNumber>
<paymentToken>eyJ2ZXJzaW9uljoiUINBX3Yxiwic2lnbmF0dXJljoiTUIBR0NTcUdTSWIzRFFFSEFxQ0FNS
UFDQVFFeER6QU5CZ2xnaGtnQlpRTUVBZ0VGQURDQUJna3Foa2lHOXcwQkJ3RUFBS0NBUIJRDVqQ0NB
NHVnQXdjQkFnSUIhR0QybWRuTXB3OHdDZ1JS29aSXpqMEVBd0I3ZWpFdU1Dd0dBMVVFQXd3bFFYQn
diR1VnUVhCd2JHbGpZWfJwYjI0Z1NXNTBaV2R5WWhScGlyNGdRMEVnTFNCSE16RW1NQ1FHQTFVRUN3
d2RRWEJ3YkdVZ1EyVnlkR2xtYVdOaGRHbhZiaUJCZfhsb2lzsBkSGt4RXpBUkjnTlZCQW9NQ2tGd2NHe
GxJRWx1WXk0eEN6QUpCZ05WQkFZVEFsVIRNQjRYRFRFMk1EWXdNekU0TVRZME1Gb1hEVEI4TURZd01
qRTRNVFkwTUZvd1lqRW9NQ1IHQTFVRUF3d2ZaV05qTFhOdGNDMWljbTlyWlhJdGMybG5ibDIWUXpRdF
UwRk9SRUpQV0RFVU1CSUdBMVVFQ3d3TGFVOVRJRK41YzNSbGJYTWhFekFSQmdOVkBb01Da0Z3Y0d4

```

bElFbHVZeTR4Q3pBSkJnTlZCQVIUQWxWVE1Ga3dFd1lIS29aSXpqMENBUVlJS29aSXpqMERBUWNEUWd
BRWdqRDIxOE9jOTE0Z0xGRFptMFVTNWpmaXFRSGRiTlBnc2MxTFVtZVkrTTIPdmVnYUphakNla3d6M2M
2T0twYkM5cStoa3dORnhPaDZSQ2JPbFJzU2xhT0NBaEV3Z2djTk1FVUdDQ3NHQVFVRk3RUJCRGt3TnpB
MUJnZ3JCZ0VGQIFjd0FZWXBhSFlwY0RvdakyOWpjM0F1WvhCd2JHVXVZMjl0TDI5amMzQXdOQzFoY0hC
c1pXRnBZMkV6TURjd0hRWURWUjBPQkJRUZBSwtNQXvhN3UxR01aZwtwbG9wbmtKeGdoeEZNQXdh
QTFVZEV3RUIvd1FDTUFBd0h3WURWUjBqQkJnd0ZvQVVJL0pKeEurVDVPOG41c1QyS0d3L29ydlMa3N3
Z2dFZEJnTIZIU0FFZ2dFVU1JSUJFRENDFQVF3R0NTcUdTSWlZWTJRRkFUQ0lvakNCd3dZSUt3WUJCUVVIQW
djd2diWU1nYk5TWld4cFIXNWpaU0j2YmlCMGFHbHpJR05sY25ScFptbGpZWFJsSUdKNUlHRnVIU0j3WVhK
MGVTQmhjM04xYldWeklHRmpZMIZ3ZEdGdVkyVWdiMllnZEdobEIIUm9aVzRnWVhCd2JHbGpZV0pzWINC
emRHRnVaR0Z5WkNCMPYSnRjeUj0Ym1RZ1kyOXVaR2wwYVc5dWN5QnZaaUlxyzJvc0IHTmxjbJwWm1
saliYUmxJSEJ2YkdsamVTQmhibVFnWTJWeWRHbG1hV05oZEsdsmJpQndjbUZqZEdsalpTQnpkR0YwWlcx
bGJuUnpMakEyQmdnckJnRUZCUWNDQVJzWFIUjBjRG92TDNkM2R5NWhjSEJzWIM1amlyMHZZMIZ5Zed
sbWFXTmhkR1ZoZFhSb2lZSnBkSGt2TURR0ExVWRId1F0TUNzd0thQW5vQ1dHSTJoMGRlQTZMeTlqY21
3dVIYQndiR1V1WTI5dEwyRndjR3hsWVdsallUTXVZM0pzTUE0R0ExVWREd0VCL3dRRUF3SUhnREFQQmd
rcWhraUc5Mk5rQmgwRUFnVUFNQW9HQ0NxR1NNNDICQU1DQTBrQU1FWUNJUURhSEdPdWkrWDJUND
RSNkdWcE43bTJuRWNyNIQ2c01qT2haNU51U28xZwd3SWhBTDFhKy9ocDg4REtKMHN2M2VUM0Z4V2N
zNzF4bWJMS0QvUUozbVdhZ3JKTk1JSUM3akNDQW5XZ0F3SUJBZ0lJU1cwndnZ6cVkyGN3Q2dZSUtvWkI6
ajBFQxdJd1p6RWJNQmtHQTFRUF3d1NRWEJ3YkdVZ1VtOXZkQ0jEUVNBdEIfY3pNU1I3SkFZRFZRUUxE
QjFCY0hCc1pTQkRaWEowYVdacFkyRjBhVz1SUVGMWRHaHZjbWwwZVRFVE1CRUdBMVVFQ2d3S1FYQn
diR1VnU1c1akxqRUXNQWtHQTFRUJoTUNWVk13SGhjTk1UUxdOVEEytWpNME5qTxidXaGNOTWprd05
UQTJNak0wTmpNd1dqQjZNUzR3TEFZRFZRUUREQ1ZCY0hCc1pTQkjjSEJzYVdOaGRhbHZiaUJKYm5SbFo
zSmhkR2x2YmlCRFFTQXRJRWN6TVNZd0pBWURWUVFMREIxQmNIQnNaU0jEWlhKM GFXWnBZMkYwYvc
5dUIFRjFkR2h2Y21sMGVURVRNQkVHQTFRRUNnd0tRWEJ3YkdVZ1NXNWpMakVMTUfrR0ExVUVCaE1DV
IZNd1dUQVRCZ2NxaGtqT1BRSUJCZ2dxGtqT1BRTUJCd05DQUFUd0Z4R0VHZGRraGRVYVhpV0JCM2JvZ
0tMdjNudXVUZUNOL0V1VDRUTlcxV1piTmE0aTBKZDJEU0pPZTdvSS9YWVh6b2pMZJ0bWNMN0k2Q21F
LzFSRm80SDNNNSUgwTUVZR0NDc0dBUVVGQndFQkJeb3dPREEYQmdnckJnRUZCUWN3QVIZcWFIUjBjRG
92TDI5amMzQXVZWEJ3YkdVdVkyOXRMMjIqYzNBd05DMWhjSEJzWlhKdmIzUmpZV2N6TUIwR0ExVWREZ
1FXQkjRajhrbkVUVNBrN3lmbXhQWW9iRctpdS8wdVN6QVBCZ05WSFJNQkFmOEVCVEEQVFILE01COEdB
MVVksXdrRWU1CYUFGTHV3M3FGWU00aWFwSXFaM3I2OTY2L2F5eVNyTURjR0ExVWREd1F3TUM0d0xLQ
XFvQ2IHSm1oMGRlQTZMeTlqY213dVIYQndiR1V1WTI5dEwyRndjR3hsY205dmRHTmhaek11WTNKc01B
NEdBMVvKRhdFQi93UUVBd0lCQmpBUUJnb3Foa2lHOTJOa0JnSU9CQUIGQURBS0JnZ3Foa2pPUFFRREFnT
m5BREjrQWpBNhozS0RVUmFac1liN05jTld5bUsvoUJmdDJROTFUYUtPdnZHY2dWNUN0NG40bVBIYldaK1
kxVUVoajUzcHd2NENNREi0MvvRaHNLTUZkMnhkOHpnN2tHzjIGM3dzSVcyV1Q4WnlhWUITYjFUNGVuM
GjtY3ViQ1iraFIRYVpEd21TSFFBQU1ZSUJYakNDQVZvQ0FRRXdnWVl3ZWPfdU1Dd0dBMVVFQXd3bFFYQ
ndiR1VnUVhCd2JHbGpZWfjwYj0Z1NXNTBaV2R5WVhScGlyNGdRMEvnTFNCSE16RW1NQ1FHQTFRUN
3d2RRWEJ3YkdVZ1EyVnlkR2xtYVdOaGRhbHZiaUJCZFrBz2lZSnBkSGt4RXpBUkJnTlZCQW9NQ2tGd2NH
eGxJRWx1WXk0eEN6QUpCZ05WQkFZVEFsVIRBZ2hvWBhWjjeW5EekFOQmdsZ2hrZ0JaUU1FQWdFRk
FLQnBNQmdHQ1NxR1NJYjNEUUVKQXpFTEJna3Foa2lHOXcwQkj3RXdiQVIKS29aSWh2Y05BUwtGTVE4W
ERURTJNEV5T0RFd05UUxhNMW93THdZSktrWklodmNOQVFrRU1TSUVJSEMvVVBRCWNzOEereDBYSFh
4UDdON1dMY3hiKzV4Wk9POHVydGhLaDISTE1Bb0dDQ3FHU000OUjBTUNCRI3UkFJZ1BXZ0RuK2Ixd3A
rSGFqNWR5MUJWt3FTODVqVVJMVA2NkhYMWtdTVtd0lDSUZ6MXkrZ1p0bEEzdXRJNkhFUNKMTFIUU
JYc3h5ckFpdIJtETsQ2kySS9BQUFBQUBQSlsImhIYWRlci6eyJ3cmFwcGVkS2V5ljojWHNQRWpWWXIwW
GZWTDY2RlgrV1lySVBCRU9FOHdUVGtrWEtdE14Y3grb0NDbGk4OHNyeHhYRVpYRGU3T0ZSUXVEcENF
WStmenpyMkwzRm55NWZnQjdMY2JlZXZIVHpnDGRXQUZBbTISQJ1NnBNMTNhSIExdVZUmdjNWEybKV
FNWxxVEtLbnhva0FIOUV0S1Bzc0NSUVRHakR0ZnZhSURGenovbFFqNW5xQmt4eljoUXVNZzRpTUE5NU
1ycHFRMIzaOExTRmE1QjkyRi9DWjNMdTjtYkZXTk12VkdmV2pPQTjzTGx6Rzc1aUj0Y0IRNzE0V0twTEJrZk
RuUjU2OU8yZWt50DBjaVk0Z0ZGc3I4R1FtSUI1Sw1oaHErbUIUZmtlMEtrWHY1MUZwcTISVG10ZTlJUFbh
eGxWN1Z5OEswOVlsTkFGN0hYVGhab21NYjF3Rnd3PT0iLCJlcGhlbWVYWyQdWjsaWNLZXkiOm51bGws
InB1YmwpY0tleUhdc2giOijqQUjpSGRVQjZDNWZkeWEvL0NnVHJ5MIBhajj0L3VZUWxVTUFyeGYzNStNPSI
slnRyYW5zYWN0aW9uSWQiOijhNzdjYjg0OTc2OTlhZjkxYTlZmFjODNjZDJmMGNIMmVmY2EzOTkzYTkxN
zNkYzM4ZGlzNjVjM2VjZmlxOWJlIn0slmRhdGEiOjRdGIXMFovV1k2dTZhQnV1RHvnYmVKbTZhODhoNnM

4dFk5cHlidjRzcVd1ZHq3NmtQNWlyVC9ZdHRkZDM2WXRDalZsTlj2RWwvSWo3MmhUL0xrSkFsdnIMTmF
4U1hjU2dQUnd5NEhvYytrRTFWY0RodG1uTuS5cmZlZ0dIT2phWUJDQW4yVTBNL0RhBGNEx0JXVDVLNn
ZzT0NCZUo1dE9rNFRTdHBYYUI5Qzl2eXo5anorYSthVGNGdkVNvJlkNm1hSjF0ZEV3QkMxd2xLaDhEWtC
2UFZHdHdxMnlPZmxuNmVmN1d6M3dITkdLeEN1RytHVGpmZnVXcGVvdThNM0hpeIZWaGh5MFJLeCtKZ
3p3L2VvcDR1aTjSTENtaFlzeG5XVHJWN1FyMGFWUFhkcTJuUVhrendUMkwzT0dpb2ZST3NZOWx3TEVla0
ZFR3dHTnMyc2IzTHk3cFVTQWFMenJIWXJ1K1UyanVzbzZLN2hFVDhxd2tZYlljek9xUVhnQkRweVcyOGFC
Y21ZMXIIUTR3TG5IU0pnTIA1Rm5tbjU0MVBlD2RYS29McXdPeDQxVDRoM0VIZzNneVpYRFpCNzk0VVjkV
XhwNzZ2b0QyOHIVcXhSN3QrUFJpc1E4PSJ9</paymentToken> <preAuth>0</preAuth>
<recurrent>0</recurrent> <recurrentInitialize>?</recurrentInitialize> </arg0> <orderBundle>
<customerDetails> <phone>+79123456789</phone> <inn>516974792202</inn> <passport>4507
443564</passport> </customerDetails> <!- Contents of the cart -> <cartItems> <!- Zero or more
repetitions: -> <items positionId=<<1>> <name><<SMALL>></name> <quantity
measure=<<0>>1</quantity> <itemCode>270_235.00</itemCode> <itemPrice>23500</itemPrice>
<tax> <taxType>0</taxType> <taxSum>0</taxSum> </tax> <itemAttributes> <attributes
name=<<nomenclature>>010463003407001221CMK45BrhN0WLf</attributes> <attributes
name=<<paymentMethod>>1</attributes> <attributes name=<<paymentObject>>30</attributes>
<attributes name=<<agent_info.type>>7</attributes> <attributes
name=<<agent_info.paying.operation>>testoperation</attributes> <attributes
name=<<agent_info.paying.phones>>+79123456789</attributes> <attributes
name=<<agent_info.paymentsOperator.phones>>+79123456789</attributes> <attributes
name=<<agent_info.MTOperator.phones>>+79123456789</attributes> <attributes
name=<<agent_info.MTOperator.name>>MT operator</attributes> <attributes
name=<<agent_info.MTOperator.address>>Moscow</attributes> <attributes
name=<<agent_info.MTOperator.inn>>8634330204</attributes> <attributes
name=<<supplier_info.phones>>+79123456789</attributes> <attributes
name=<<supplier_info.name>>Supplier</attributes> <attributes
name=<<supplier_info.inn>>287381373424</attributes> <attributes
name=<<excise>>10.0</attributes> <attributes name=<<country_code>>810</attributes>
<attributes name=<<declaration_number>>12332234533</attributes> <attributes
name=<<userData>>user data</attributes> <attributes
name=<<markQuantity.numerator>>1</attributes> <attributes
name=<<markQuantity.denominator>>2</attributes> <attributes
name=<<sectorallItemProps[0].federalId>>001</attributes> <attributes
name=<<sectorallItemProps[0].date>>10.10.2021</attributes> <attributes
name=<<sectorallItemProps[0].number>>123/4567</attributes> <attributes
name=<<sectorallItemProps[0].value>>value1</attributes> <attributes
name=<<sectorallItemProps[1].federalId>>003</attributes> <attributes
name=<<sectorallItemProps[1].date>>10.10.2021</attributes> <attributes
name=<<sectorallItemProps[1].number>>321/4567</attributes> <attributes
name=<<sectorallItemProps[1].value>>value2</attributes> </itemAttributes> </items> </cartItems>
</orderBundle> </mer:googlePay> </soapenv:Body> </soapenv:Envelope> </suh> ===== Пример
ответа ===== Successful payment === <suh xml> <soap:Envelope
xmlns:soap= <soap:Body> <ns1:googlePayResponse
xmlns:ns1= <return>
<success>true</success> <data> <orderId>ef72d37b-d87b-75f6-a87a-364e000d813a</orderId>
<transactionId>0cb952bc-af65-45c5-8674-b5e2b556ae34</transactionId> </data> <orderStatus
orderNumber=<<138003>> orderStatus=<<2>> actionCode=<<0>> actionCodeDescription=<<>>
amount=<<23500>> currency=<<643>> date=<<2022-01-25T17:12:52.302+03:00>> ip=<<10.99.50.35>>
errorCode=<<0>> <attributes name=<<mdOrder>> value=<<ef72d37b-d87b-75f6-
a87a-364e000d813a>> <cardAuthInfo maskedPan=<<411111**1111>> expiration=<<202412>>
cardholderName=<<Surname Name>> approvalCode=<<123456>> paymentSystem=<<VISA>>

```
<secureAuthInfo> <eci>7</eci> <threeDSInfo> <cavv>TVRJek5EVTJOemc1TVRJek5EVTI=</cavv>
</threeDSInfo> </secureAuthInfo> </cardAuthInfo>
<authDateTime>2022-01-25T17:12:52.575+03:00</authDateTime>
<authRefNum>691879196645</authRefNum> <paymentAmountInfo paymentState=«DEPOSITED»
approvedAmount=«23500» depositedAmount=«23500» refundedAmount=«0» feeAmount=«0»
totalAmount=«23500»/> <bankInfo bankName=«TEST BANK» bankCountryCode=«RU»
bankCountryName=«Россия»/> <chargeback>false</chargeback> <operations amount=«23500»
cardHolder=«Surname Name» authCode=«123456»/> </orderStatus> </return>
</ns1:googlePayResponse> </soap:Body> </soap:Envelope> </sxh> === Failed payment ===
<sxh xml> <soap:Envelope xmlns:soap=«http://schemas.xmlsoap.org/soap/envelope/»>
<soap:Body> <ns1:googlePayResponse
xmlns:ns1=«http://engine.paymentgate.ru/webservices/merchant»> <return>
<success>false</success> <error> <code>10</code> <description>Invalid parameter
[orderNumber]</description> </error> <orderStatus errorCode=«0»/> </return>
</ns1:googlePayResponse> </soap:Body> </soap:Envelope> </sxh>
```