Request for order payment by binding (paymentOrderBinding)

The request used for making a payment by binding is paymentOrderBinding.

Use the following URL to connect to the Test Service (WSDL): https://3dsec.sberbank.ru/payment/webservices/merchant-ws?wsdl.

Request parameters

Name	Туре	Mandatory	Description	
md0rder	ANS36	YAC	Order number in the payment gateway. Unique within the payment gateway.	
bindingId	AN255	res	The identifier of the previously created binding. Can only be used if the merchant has permission to work with bindings. I this parameter is passed in the given request, it means that 1. The given order can be paid only using a binding; 2. The payer will be redirected to the payment page on which only entering CVC is required.	

Name	Туре	Mandatory	Description		
			Additional tag with the attributes for passing additional parameters. The fields for additional information and its subsequent storage. These fields can be submitted for processing by the bank for further display in the registers. By default, the order number orderNumber and its description orderDescription are passed to the bank for processing (no more than 99 characters, «%» (percentage), «+» (plus), «\r» (carriage return) and «\n» (line feed) are prohibited for using). Enabling the functionality is possible upon agreement with the Bank during the integration period. To pass N parameters, a request must contain N params tags, where the name attribute contains the parameter name and value attribute contains its value:		
			Name	Туре	Description
params	See column with the description.		Name name Type AN20 Type2 ANS255 Type3 A7 Type4 ANS100 Description REST Name of the additional parameter. REST Online Lending The attribute name, always takes the value of mdOrder. WS Name of the additional parameter. Spasibo Name or the description of an item in any format. Spasibo2 Name of the parameter describing the details of a line item	ANS255	Name of the additional parameter.
			value		The value of the additional parameter is up to 1024 characters.
			It is forbidden to pass reserved names in the parameter (if they are passed, the order may be rejected): sbrf_spasibo:amount_bonus sbrf_sbermiles:amount_bonus loyaltyid		

Name	Туре	Mandatory	Description
language	A2	No	Language in the ISO 639-1 encoding. If the language is not specified, the default language defined in the store settings is used.
ip	ANS39	Yes	IP-address of the buyer. IPv6 is supported in all requests (up to 39 characters).
cvc	N3	No	This parameter is mandatory, if Can process payments without confirmation of CVC is not selected for a Merchant.
email	ANS40	No	Customer's email address.

Response parameters

Name	Туре	Mandatory	Description
redirect	ANS*	No	On a successful response. In the case of a payment without the need for authentication to the ACS – URL to which redirect is performed after the payment. In case of a 3D-Secure payment, the URL to return to ACS.
info	ANS*	No	On a successful response. Result of a payment attempt. The available values are presented below. Your payment has been processed, redirecting Payment declined. Check the entered data and that there are enough funds on the card and repeat the operation. Redirecting Sorry, the payment cannot be processed. Redirecting Payment declined. Please contact the Merchant. Redirecting Payment declined. Contact the bank that issued the card. Redirecting Operation is impossible. Cardholder authentication completed unsuccessfully. Redirecting No connection to the bank. Try again later. Redirecting The data entering period has expired. Redirecting No response from the bank. Try again later. Redirecting
errorCode	ANS3	Yes	Error code.
errorMessage	AN512	No	Error description in the language passed in the language parameter in the request.
errorTypeName		No	Parameter required by the front page to define the error text. Mandatory in case of unsuccessful payment. Possible values can be viewed here
acsUrl	AN512		Redirect address to the address of the ACS server.
paReq	AN512	No	Request for the payer authentication.

Error codes

Error code	Error text	
0	The request has been processed without system errors.	
1	[mdOrder] is empty.	
1	[bindingId] is empty.	
2	The binding is not found.	
2	Access denied.	
5	The user must change the password.	
5	All payment attempts were used.	
7	System error.	

Examples

Request example

Response example

