

Request for a binding deactivation (unBindCard)

The request used for making an existing binding inactive is unBindCard.

Use the following URL to connect to the Test Service (WSDL):

<https://3dsec.sberbank.ru/payment/webservices/merchant-ws?wsdl>.

In this document, the following data type conventions are used when describing request and response parameters:

- A<n> - a sequence of Latin letters of length <n>;
- A..<n> - a sequence of Latin letters with a length not exceeding <n>;
- N<n> - a sequence of digits of length <n>;
- N..<n> - a sequence of digits with a length not exceeding <n>;
- AN<n> - a sequence of Latin letters and numbers of fixed length <n>;
- AN..<n> - a sequence of Latin letters and numbers with a length not exceeding <n>;
- ANS<n> - a sequence of Latin letters, numbers and characters of fixed length <n>
- ANS..<n> - a sequence of Latin letters, numbers and characters with a length not exceeding <n>;
- UTC - date and time, in this case: the date must be passed without specifying the time zone, Moscow time, for the SOAP protocol, the standard encoding xs: dateTime is used.

Request parameters

Name	Type	Mandatory	Description
bindingId	AN..255	Yes	The identifier of the previously created binding. Can only be used if the merchant has permission to work with bindings. If this parameter is passed in the given request, it means that: 1. The given order can be paid only using a binding; 2. The payer will be redirected to the payment page on which only entering CVC is required.

Response parameters

Name	Type	Mandatory	Description
errorCode	ANS..3	No	Error code.
errorMessage	AN..512	No	Error description in the language passed in the language parameter in the request.

Error codes

Error code	Error text
0	The request has been processed without system errors.
2	Wrong binding state.

Error code	Error text
2	The binding is not found.
5	Access denied.
5	The user must change the password.
7	System error.

Examples

Request example

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:mer="http://engine.paymentgate.ru/webservices/merchant">
  <soapenv:Header/>
  <soapenv:Body>
    <mer:unBindCard>
      <bindingId>fd3afc57-c6d0-4e08-aaef-1b7cfeb093dc</bindingId>
    </mer:unBindCard>
  </soapenv:Body>
</soapenv:Envelope>
```

Response example

```
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <ns1:unBindCardResponse
xmlns:ns1="http://engine.paymentgate.ru/webservices/merchant">
      <return errorCode="0" errorMessage="Successful"/>
    </ns1:unBindCardResponse>
  </soap:Body>
</soap:Envelope>
```