

Deletion of the card from the list of saved ones

In this document, the following data type conventions are used when describing request and response parameters:

- string – string;
- array – data array;
- object – data object;
- data – date;
- boolean – boolean (logical) data type;
- int. (integer) – integer data type;
- amount – a numeric data type (amount).

Request parameters:

Parameter	Type	Description	Example
type	string	Specifying the entity type, the following values are possible: • client – customer; • binding – binding.	binding
uuid	string	The entity identifier of the specified type, the length is 32 bytes.	693EABCEDEFF4107B885243559381312

Request format:

```
POST /api/delete HTTP/1.1
```

```
Host: 3dsec.sberbank.ru/sbersafe
```

```
Authorization: <accessToken>
```

```
Content-Type: application/json
```

```
Accept: application/json; version=1.0
```

```
Content-Length: <content-length>
```

```
{  
  
  "type": "<type>",  
  
  "uuid": "uuid"
```

```
}
```

Response parameters:

Parameter	Type	Description	Example
requestId	string	Request identifier.	gbhjnkm-rdcfgv-hbjnkm-7689ui-okp3ew
status	string	Indication of the status of the request processing result	SUCCESS

Response format:

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: <content-length>
Cache-Control: no-store

{
  "requestId": "<requestId>",
  "status": "<status>"
}
```